

Arco Chills Overspec

Specification Sheet

Product Code: 3G0100

For further information:

Arco Ltd, PO Box 21, Waverley Street, Hull, HU1 2SJ

www.arco.co.uk

Tel: 01482 222522 Fax: 01482 28536

GENERAL SPECIFICATIONS(mm)

Lens thickness: 2.03 mm


PD: 68 mm

Lens Base: 2 curve Weight: 33 gm

Lens size vertical: 49.5 mm Lens size diagonal: 58.4 mm

Bridge: 19.5 mm

Temple length (lens-tip): 152-166 mm Overall Width (hinge-hinge): 148 mm Closest point between lens: 13.9 mm Closest point between temple tips: 82 mm



COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	One piece molded lens, integral side
		shield and brow guard
Side Shields	Polycarbonate	Integral to the lens
Nose piece	Polycarbonate	Integral to the lens
Ratchet	Nylon	Angle adjustment
Component	Nylon	Clipped with ratchet
Sleeve	PC Compound	4-position length adjustment
Temple	Nylon	Soft temple tips snapped onto the temple
Temple tips	PVC	
Hinge	Nylon/ PC Compound	3 Barrel type
Screw	Stainless Steel	Standard hinge screw

SPECIAL FEATURES

- Functional and stylish over spec that fits most of the prescription lenses
- Built-in brow guard and side shield.
- Lens inclination and temple length are adjustable for personal fit
- Soft temple tips for extra comfort. .
- Anti-scratch and anti-mist coated lens.
- 100% pure polycarbonate lens filters out more than 99.9% of harmful light.
- CE certified to EN166, optical class 1 & low energy impact F