

POLYESTER STRAPPING

Reggia in Poliestere - Polyester Umreifungsband-Feuillard de cerclage en polyester-Fleje de poliester para flejar

DATA SHEET

Scheda tecnica - Datenblatt - Fiche de donnees - Hoja de datos

PRODUCT TYPE:		19 X 0,90 Z
Tipo - Typ -Designation -Tipo		
CORE (mm) :		405x160
Mandrino - Kern - Mandrin - Mandril		
COLOUR:		GREEN
Colore -Farbe - Couleur - Color		
Surface		embossed
Superficie - Oberflaeche - Surface -Superficie		
Goffrata - Gerpraegt- Gaufrée - Grafilado		
meters/coil (m)		1000
Metraggio/Bobina -Meter/Spule -Metrage/Bonine - Metros/Rollo		
		± 2,5%
		Maximum 19,00
WIDTH,		Nominal 18,50
Larghezza -Breite - Lateur - Anchura		
		Minimum 18,00
		Maximum ,94
THICKNESS,		Nominal ,90
Spessore - Dicke - Epaisseur - Grueso		
		Minimum ,86
		Maximum 20,80
GRAMM METER		Nominal 20,40
Grammo metro -Gramm meter - Gramme metre - Metro del gramo		
		Minimum 20,00
AVERAGE BREAKING STRENGTH,		Kg 653
Resistenza media - Durchschnittsrebfestigkeit - Résistance moyenne -		
		[N] 6404
		Maximum 20
ELONGATION AT BREAK,		Nominal 15
Allungamento - Durchschnittsdehnung - Allongement - Alargamiento		
		Minimum 10
QUALITY STANDARD		UNI EN ISO 9001
Qualità standard - Qualitätsstandard - Standard de qualite -		
Date of issue		
Data - Ausgabedatum - Date - Fecha		
12/01/2018		