



tesa[®] extra Power Perfect

BNR 36341, 56339, 56342, 56343, 56344

tesa cloth tape extra Power Perfect is a premium quality repair tape designed for demanding indoor and outdoor applications.

Features

- Cloth tape all professional solutions like handicrafts, fastening, bundling, strengthening, marking and much more
- Highest and perfect adhesive power, also on rough and oily surfaces
- For permanent high resilience and long-term results
- Weather-resistant cloth tape for in-and outdoor applications
- Tear-resistant but tearable by hand
- Can be written on
- Available in a wide range of colours

Product Properties

- | | | | |
|-----------------------------|---------------------------|----------------------|--------------------------------------------------------------------------------------------------------------|
| • Applicationfield | Home, Garden, Car, Garage | • Solvent free | yes |
| • Tear resistant | yes | • Suitable surfaces | Tiles, Glass, Even wood, Plaster, Steel, Stone, Brick, Acrylic glass, Metal, Most plastics, Paper, Cardboard |
| • Writable | yes | • Reusable | no |
| • Hand tearable | yes | • Refillable | no |
| • Spare part service | no | • Waterproof | yes |
| • UV-resistant | yes | • Recyclable | no |
| • Water resistant | yes | • Shape | Roll |
| • Humidity resistant | yes | • Batteries required | no |
| • Oil- and grease-resistant | yes | • Batteries included | no |
| • Ozone resistant | yes | | |

Technical Data

- | | | | |
|---------------------------|----------------------|--------------------------|----------|
| • Application temperature | from 10°C up to 50°C | • Tensile strength | 100 N/cm |
| • Area of use | In- and Outdoor | • Total thickness | 310 µm |
| • Ecofriendly packaging | yes | • Temperature resistant | yes |
| • Residue-free removable | yes | • Age-resistant | yes |
| • Adhesive strength | Very high adhesion | • Temperature resistance | 140 °C |
| • Type of adhesive | natural rubber | up to | |
| • Backing material | Acrylic-coated cloth | • Tensibility | 13 % |
| | | • Hazard material | no |

tesa[®] extra Power Perfect

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=36341>