

TECHNICAL DATA SHEET

CUSTOMER: Antalis A/S; Bastrupgaardvej 8-10; 7500 Holstebro; DENMARK

PRODUCT:

BOTH SIDE PRINTED, DKT BAG, WHITE, PROTECT FUTURE

PRODUCT NO.: A370036

DIMENSIONS: 400 x 450+50 x 0,045 mm

MATERIAL:

Film is made of recycled polyethylene, white masterbatch and additives.

DIMENSIONS:

Film thickness: 0,045 mm, tolerance: $\pm 10\%$

Bag width: 400 mm, tolerance: $\pm 5\%$

Bag length: 450 mm, tolerance: $\pm 5\%$

Bottom gusset: 50 mm, tolerance: $\pm 5\%$

PHYSICAL CHARACTERISTICS:

Density: 0,916 – 0,925 g/cm³

Tensile strength at break (ASTM D882): MD:20 MPa

TD: 18 MPa

Elongation at break (ASTM D882): MD >250 %

TD >450 %

PACKAGING: 250 pcs /box

STORAGE CONDITIONS:

Store in a dry place, the film should not be exposed to direct sunlight, before use, the film will be tempered in temp. 16 - 20 °C for a minimum of 24 hours.

GENERAL INFORMATION:

This datasheet is for informational purposes only and applies to this item only. For more detailed information, please contact our sales department.

Hrušica, 20.7.2021

Josip Maurič
R&D Manager

Petra Grželj Polh
R&D and ecology
