



Tork Advanced Aftøringspapir 430 Combi Performance



Fordel

- Aftøringspapir med stor kapacitet, ideelt i alle hygiejniske miljøer
- Hurtig opsugning af væske øger effektiviteten og sparer tid
- Stærkt og sikkert
- Højere produktivitet
- Lavere omkostninger
- Bedre hygiejne
- Overholder levnedsmiddelforanstaltningerne - godkendt til kontakt med levnedsmidler (ISEGA).



Food contact approved certified by a thi



Produktspecifikation

Artikel	System	Rullelængde	Rullediameter	Antal ark	Indvendig kerediameter	Lag	Tryk	Prægning	Farve
130062	W1 - Aftøringspapir væg-/gulv-/standardsystem, W2 - Aftøringspapir kombirullesystem	170 m	26.2 cm	500	7.1 cm	2	Nej	Ja	Hvid

Beskrivelse

Tork Advanced 430 (aftøringspapir til engangsbrug) tilbyder en effektiv aftørring og passer til de fleste miljøer i industrien. Papiret til allround brug er ideelt til værksteder og produktionslinjer for eksempel til aftørring af olie og fedt, til at tørre sine hænder i eller rengøring af maskiner. Aftøringspapiret er også godt til hygiejnemæssige områder samt tilberedning af levnedsmidler o. lign.



Forsendelsesdata

Forbrugerenhed

EAN	7322540183603
Stk.	1
Højde	235 mm
Bredde	262 mm
Længde	262 mm
Volumen	16.1 dm ³
Nettovægt	1598 g
Bruttovægt	1639 g

Transportenhed

EAN	7322540183719
Stk.	2
Forbrugerenheder	2
Materiale	Shrink
Højde	235 mm
Bredde	262 mm
Længde	524 mm
Volumen	32.3 dm ³
Nettovægt	3.20 kg
Bruttovægt	3.33 kg

Palle

EAN	7322540189407
Stk.	96
Forbrugerenheder	96
Højde	2030 mm
Bredde	800 mm
Længde	1200 mm
Volumen	1.5 m ³
Nettovægt	153.41 kg
Bruttovægt	160.03 kg



Miljø

Content

Virgin pulp fibres

Chemicals

Material

Virgin fibre

Virgin pulp fibres are produced out of softwood or hardwood. The process is either sulphite or sulphate delignification, meaning that e.g. lignins and resins are removed from cellulosic material.

Bleaching of fibres

Bleaching is a cleaning process of the fibres and the aim is to achieve a bright pulp, but also to get a certain purity of the fibre in order to achieve the demands for hygiene products and in some cases to meet the requirements for food safety.

There are different methods used today for bleaching ECF (elementary chlorine free) where chlorine dioxide is used, and TCF (totally chlorine free) where ozone, oxygen and hydrogen peroxide is used.

Chemicals

The chemicals used in the process as well as the functional chemicals are assessed from an environmental, occupational health and safety and product safety point of view .

The used functional chemicals are:

Wetstrength agent

Dry strength agent

Dye = if coloured

Fixing agents

Fluorescent whitening agent

Glue = if used

The process chemicals are:

Antipitch

Protection agent

Yankee coating

Defoamer

Dispersing agents and surfactants

pH and charge control



Tork Advanced Aftøringspapir 430 Combi Performance

Retention aids

Broke treatment chemicals

Drainage aid

Food Contact

This product fulfils the legislative requirements for Food Contact materials, confirmed by external certification performed by ISEGA. The product is safe for wiping food contact surfaces and may also come occasionally into contact with foodstuffs for a short period of time.

Packaging

Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes

Environmental label = Ecolabel

This product is certified according to FSC

Date of issue 2006-06-12

Revision date 2011-09-02 2011-03-14, 2011-11-16

SCA Hygiene Products AB, 405 03 Göteborg, SE

Production

Material produced at Mannheim mill and product converted at Kostheim mill, Germany, certified according to ISO 9001:2000, ISO 14001 and EMAS

Disposal / destruction of used product

This product is mainly used for industrial processes and might through use be contaminated with different substances. This will determine how the used product will be handled / disposed of /destroyed. The product itself is suitable for incineration. Contact local authorities before destruction.