## ECOS MOULD OP180-35/CBNN

## G9F08192

	Technical data	
Product family:	Ecos	
Bottom A:	170 mm. +/- 1 mm.	
Тор В:	181 mm. +/- 1 mm.	
Rim C:	186 mm. +/- 1 mm.	
Rim D:	194 mm. +/- 1 mm.	
Height:	35 mm. +/- 1 mm.	
Weight:	11,5 gr. +/- 5%	
Description:	Bleached pure cellulose light cardboard, inner side laminated with polyester film of 7 my, through monocomponent adhesive, printed both outside and inside.	
Tot. Gr/sqm:	217 gr. +/- 5%	
Printing:	Full surface printing (both sides)	
Ink:	Black resistant to alcohol (rubbing) and to heat (200°) Our inks and promoter are in conformity with the requirement	ents stated by EUPIA
Adhesive:	Monocomponent adhesive used for laminating paper or car	dboard.
Additive:	Water based varnish resistant to heat and humidity.	
Heat resistance:	180° ÷ 220°	
Health Legislation:	Please refer to "Conformity declaration concerning paper and cardboard material to be in direct contact with foodstuffs".	
Box	mm. 595*400*415	
Volume	m3 0,099	
Quantity per box	720 pz. (180 pz.*4 file)	
Pallet	EUR-PAL 80 * 120	
Lay-out	4 boxes per 4 piani tot. 16	
Quantity per pallet	11.520 pz.	
Label	with data for product identification	
Protective film	Low density polyethylene used for packaging	

Prepared	Approved	Date	Rev.	Modifications executed:
BM	Aver	01/03/2009	2	
QUALITY MANAGER Ing. MEREGALLI				

Customer's approval						
amp and signature:						
ate:						
die.						

PLEASE SEE OVERLEAF FOR TECHNICAL DRAWING

