

Scotch®

Performance BOPP Box Sealing Tape 3739

Product Data Sheet

Updated : July 2000

Supersedes : June 1998

Product Description

3739 is a performance box sealing tape with a high strength polypropylene film backing and hot melt synthetic rubber-resin adhesive.

Applications

Mainly used for single strip closure of fibreboard boxes, re-sealing and packaging of heavy weight of valuable goods. Ideally, # 3739 is best applied at room temperature and onto clean dry dust free fibreboard surfaces. Once applied, this product performs well throughout all temperatures typically encountered by packaged products in shipping and storage environments

Physical Properties

Not for specification purposes

Adhesive Type	Hot-melt Synthetic Rubber Resin
Backing	35 micron Bi-axially Oriented Polypropylene Film
Total Thickness	56 micron
Colour	Transparent, White, Brown
Storage Conditions	Store behind present stock, in a clean dry place. Temperature of 64 - 70°F (18-21°C) & 40-50% Relative Humidity are recommended. Under correct storage conditions the tape maintains its characteristics for one year (shelf life).

Recommended

Dispensers

Hand Held : H-180E, H-183, H-150 Low Noise

Automatic Case Sealers : Suitable for complete range of 3M-Matic Case Sealers

Date : July 2000
 Scotch® Performance BOPP
 Box Sealing Tape 3739

Performance Characteristics
 Not for specification purposes

Adhesion to Steel	4.5 N/10 mm
Tensile Strength at Break	60 N/10mm
Elongation at Break AFERA 4005	150 %
Static Shear	4,500+ minutes

**Features/Advantages/
Benefits**

Features

Advantages

Benefits

Bi-axially Oriented
Polypropylene Film Backing

Resists splitting when
subjected to rough handling
and absorbs impact shock

Reduces failures in box
sealing applications. Helps
assure safe delivery of
product.

High Impact Strength

Withstands normal
shipping conditions

Hot-melt Synthetic Rubber
Resin Adhesive

No dwell time necessary,
adheres immediately

Fast to apply, saves time

High initial shear adhesion
to fibreboard surfaces

Helps reduce failures in box
sealing and package
closure applications

Machine Length Rolls

Fewer roll changes on
application equipment

Increased production rate
for lower unit cost

3M and Scotch are trademarks of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Tapes & Adhesives

© 3M United Kingdom PLC 1996

3M United Kingdom PLC
 3M House,
 28 Great Jackson Street,
 Manchester,
 M15 4PA

Product Information :
 Tel 0870 60 800 50
 Fax 0870 60 700 99

3M Ireland
 3M House, Adelphi Centre,
 Upper Georges Street,
 Dun Laoghaire, Co. Dublin,
 Ireland

Customer Service :
 Tel (01) 280 3555
 Fax (01) 280 3509