



Tork Premium Specialklud Precision Cleaning Refill til Spand



Fordel

- Ideel til slutrengøring og støvfølsomme miljøer
- Kan anvendes flere gange - fleksibel og foldbar
- En stort set frugfri og meget stærk klud i praktisk spand



Produktspecifikation

Artikel	System	Rullelængde	Rullediameter	Antal ark	Lag	Tryk	Farve
90491	W10 - Handy-spand, stor	70 m	18 cm	250	1	Nej	Turkis

Forsendelsesdata

Forbrugerenhed

EAN	7322540353679
Stk.	1
Højde	175 mm
Bredde	180 mm
Længde	180 mm
Volumen	5.7 dm ³
Nettovægt	956 g
Bruttovægt	956 g

Transportenhed

EAN	7322540353686
Stk.	4
Forbrugerenheder	4
Materiale	Carton
Højde	197 mm
Bredde	375 mm
Længde	375 mm
Volumen	27.7 dm ³
Nettovægt	3.82 kg
Bruttovægt	4.31 kg

Palle

EAN	7322540357387
Stk.	216
Forbrugerenheder	216
Højde	1923 mm
Bredde	800 mm
Længde	1200 mm
Volumen	1.5 m ³
Nettovægt	206.39 kg
Bruttovægt	232.85 kg



Miljø

Content

Chemical pulp

Polyester

Chemicals

Material

Chemical pulp

Chemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.

There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free).

ECF is based on oxygen, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone.

Polyester

Polyester fibre is produced from terephthalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length.

Chemicals

Both functional and process chemicals are used. The functional chemical used is wet strength agent. The wet strength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre.

Process chemical used is a surfactant.

Production

This product is produced externally in DE.



Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destroyed. The product itself is suitable for incineration. Contact local authorities before destruction.