



Aktieselskab

POLYETHYLENEMBALLAGE UDEN OG MED TRYK I OP TIL 8 FARVER
BÆREPOSER • RULLEPOSER • POSER • SÆKKE • WICKETPOSER • FOLIER

SVEJSEGANGEN 12 • DK-2690 KARLSLUNDE • DANMARK
TLE. +45 46 15 14 00 • TELEFAX +45 46 15 36 22 • WEBSITE www.norlin.com

Karlsunde d. 19/8-2008

Erklæring om LDPEs egnethed til nedfrysning af fødevarer

Jeg skal hermed erklære at poser fremstillet af Norlip A/S til emballering af fødevarer, og fremstillet af råvarer INEOS 24F564, er velegnet til nedfrysning, under forudsætning af at folien min. er 40 My tyk, og at nedfrysningen foregår under normale forhold til maksimalt -30°. Denne LDPE råvarer INEOS 24F564 er ikke egnet til lynfrysning.
Se også dokument fra INEOS om nedfrysning af råvarer 24F564.

Med venlig hilsen

Jesper Philipsen

18th August 2008

Dear Susanne,

Subject: 24F564 LDPE

24F564 is a conventional LDPE and as such has a glass transition temperature (point at which the material becomes brittle) of -90°C. Whilst we can not make any guarantees regarding end use fitness for purpose, I can see no reason why this product is not suitable for use in freezer bag applications.

Actual fitness for purpose is dependant on many factors beyond those of the mechanical properties of the material so, as stated above, it is for the end user to determine whether the bags they produce are fit for their intended purpose.

Yours Sincerely,



Alan Sorrie
Technical Service and Development
INEOS Europe Ltd