

Product data sheet

PE hoods

Article description:

PE hoods

Article number:

1460620-000

Dimensions:

1.270 + 850 / 1.800 / 0,100 mm

Product data sheet:

209679 / Mai 2018



Antalis A/S, Bastrupgaardvej 8 - 10, 7500 Holstebro, Dänemark

1.0	Product description		Production tolerances	According to
1.1	article description:	PE hoods		
1.2	Dimensions	w: 1.270 + 850 mm l: 1.800 mm	w: 15 mm l: 3,0 %	GKV
1.3	Thickness	100 µm	5 %	GKV
	Area density	92 g/m ²	calculated	
1.4	Coloring	transparent		
1.5	Features	perforated on a roll of 50 pieces		
1.6	Printing	without		
2.0	Specifications		Production tolerances	According to
2.1	Basic commodity	Polyolefins LDPE + LLDPE + LLDPE		ISO 1043
2.2	Density	918 – 940 kg/m ³		ISO 1183-1
2.3	Melt flow index	0,3 - 1,0 g/10 min		ISO 1133
2.4	Tensile Strain at Break MD	400 – 500 %		ISO 527-3
	Tensile Strain at Break TD	500 – 600 %		ISO 527-3
2.5	Tensile Strength MD	22 – 24 N/mm ²		ISO 527-3
	Tensile Strength TD	20 – 22 N/mm ²		ISO 527-3
2.6	Sliding Coefficient			ISO 8295
	Foil – Foil	0,4 – 0,5		
	Foil – Metal	0,3 – 0,4		
2.7	Vicat Softening Temperature	90 °C		ISO 306
2.8	Melting temperature	110 °C		DSC
3.0	Other			
3.1	Production methode	Blown Film – extrusion		
3.2	Weldingability	min. 60 % of the film strength, without residues		