

Data Sheet for AirCap® ELRT

Co-Extruded plastic bubble film made from polyethylene with barrier layer. Polyethylene consists of minimum 50% recycled external regrind.

Physical Properties	Value	Unit	Tolerance
Bubbel height (under compression)	2.5	mm	±10%
Bubble diameter	9	mm	-
Surface density	31	g/m²	±10%
Dimensions	-	mm	± 2%
Amount of recycled content*	50	wt% (weight percentage)	-
Number of complete bubbles**	800	-	-
Color	As it comes***	-	-

- * PIR or PCR
- ** In an area of 300x300 mm
- *** Predominately different shades of grey/black



Sealed Air Svenska AB Påtorpsvägen 2 Box 146 57833 Aneby, Sweden scandinavia.ppcs@sealedair.com www.sealedair.com/product-care NOTICE: The data presented for this product is for unfabricated polyethylene foam product. While values shown are typical of this product, they should not be construed as specification limits. Sealed Air makes no warranties, express or implied, including without limitation, warranties of merchantability or fitness for a particular purpose, with respect to any product, information or recommendations referred to herein, and shall not be liable for any loss or damage, directly or indirectly, related to such product, information or recommendations or for consequential or incidental damages. User should test each application to determine suitability of the product for the intended use.